


Safety pin shackles

Material	drop forged high tensile steel grade 6 quenched and tempered	Packaging	
		Specification	U.S. Federal Spec. RR-C-271D type IVA class 3 - meets requirements of EN 13889
Surface finish	galvanized 6 µm - pin red RAL 3001- metric thread - hot dip galvanized upon requested - temperature range - 20°C 200°C	Identification	<ul style="list-style-type: none"> • CE • bow dim. in inch • traceability code • WLL • TIL logo
Applications	general lifting requirements		
Safety factor	see table		



WLL [Tons]	A [mm]	A [inch]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	s.f.	Weight [Kg]	Part number
2	13	1/2	21	16	84	48	17,5	6	0,36	5SL002000M
3,25	16,5	5/8	27,5	20	106	60	22	6	0,75	5SL003250M
4,75	20	3/4	32	22	126	72	26	6	1,15	5SL004750M
6,5	22	7/8	37	25	146	84,5	29	6	1,87	5SL006500M
8,5	25	1"	44	30	165	95	34	6	2,79	5SL008500M
9,5	28	1"1/8	46	33	185	108	37	6	3,58	5SL009500M
12	35	1"1/4	52	36	210	120	42	6	4,87	5SL012000M
13,5	35	1"3/8	57	40	229	132	46	6	6,36	-
17	38	1"1/2	61	42	251	146	49	6	8,60	5SL017000M
25	45	1"3/4	74	50	314	178	63	6	14,20	5SL025000M
35	50	2"	83	57	358	197	69	6	19,85	5SL035000M
55	65	2"1/2	105	70	463	260	90	6	39,60	5SL055000M
85	75	3"	127	83	556	329	95	6	62	5SL085000M
120	95	3"3/4	144	95	667	381	119	5	110	5SL098000M

